

Tragfähigkeiten
Lifting capacities
Capacités de levage
Capacidades de elevación



13.2t

DIN / ISO

| ↙ m | 10.4 m | 14.1 m | 17.8 m | 25.3 m | 32.7 m | 36.5 m | 40.2 m |
|------|--------|--------|--------|----------|-----------|---------|--------|
| 2.5 | 60.0* | | | | | | |
| 3.0 | 50.0 | 30.0 | | | | | |
| 3.5 | 44.8 | 30.0 | 30.0 | | | | |
| 4.0 | 41.0 | 30.0 | 29.0 | | | | |
| 4.5 | 37.0 | 30.0 | 27.5 | | | | |
| 5.0 | 34.3 | 30.0 | 26.2 | 17.0 | | | |
| 6.0 | 29.8 | 29.3 | 22.6 | 17.0 | 13.0 | | |
| 7.0 | 25.3 | 24.9 | 20.0 | 15.8 | 13.0 | | |
| 8.0 | 16.9 | 21.4 | 20.0 | 14.5 | 13.0 | 9.0 | 7.0 |
| 9.0 | | 18.1 | 18.4 | 13.3 | 12.0 | 8.8 | 7.0 |
| 10.0 | | 15.2 | 15.5 | 13.0 | 11.0 | 8.5 | 7.0 |
| 11.0 | | 12.9 | 13.2 | 12.6 | 10.1 | 8.3 | 7.0 |
| 12.0 | | | 12.8 | 12.1 | 9.2 | 8.1 | 7.0 |
| 14.0 | | | 9.9 | 9.8 | 7.8 | 7.6 | 6.5 |
| 16.0 | | | | 7.8 | 6.7 | 6.5 | 6.1 |
| 18.0 | | | | 6.8 | 5.8 | 5.8 | 5.3 |
| 20.0 | | | | 5.8 | 4.8 | 4.9 | 4.6 |
| 22.0 | | | | 4.9 | 4.0 | 4.1 | 4.1 |
| 24.0 | | | | | 3.6 | 3.3 | 3.6 |
| 26.0 | | | | | 3.2 | 2.7 | 3.0 |
| 28.0 | | | | | 2.9 | 2.2 | 2.5 |
| 30.0 | | | | | 2.7 | 1.8 | 2.0 |
| 32.0 | | | | | | 1.5 | 1.7 |
| 34.0 | | | | | | 1.1 | 1.4 |
| 36.0 | | | | | | | 1.1 |
| ↙ % | I | 0 | 50 | 50/100/0 | 50/100/0 | 100/0 | 100 |
| | II | 0 | 0 | 50/0/33 | 50/100/67 | 100/100 | 100 |
| | III | 0 | 0 | 0/0/33 | 50/0/67 | 50/100 | 75 |
| | IV | 0 | 0 | 0/0/33 | 50/0/67 | 50/100 | 75 |



13.2t

DIN / ISO

| ↙ m | 36.5 m + 9.0 m | | | 40.2 m + 9.0 m | | | 40.2 m + 16.0 m | | |
|------|----------------|------|------|----------------|------|------|-----------------|------|------|
| | 5° | 17° | 30° | 5° | 17° | 30° | 5° | 17° | 30° |
| 10.0 | 4.80 | | | 3.80 | | | | | |
| 11.0 | 4.80 | | | 3.80 | | | | | |
| 12.0 | 4.80 | 4.00 | 3.00 | 3.80 | 3.40 | | 2.20 | | |
| 14.0 | 4.60 | 3.75 | 2.85 | 3.60 | 3.40 | 2.80 | 2.20 | 1.80 | |
| 16.0 | 4.40 | 3.45 | 2.65 | 3.70 | 3.25 | 2.70 | 2.20 | 1.80 | 1.30 |
| 18.0 | 4.20 | 3.15 | 2.50 | 3.55 | 3.10 | 2.55 | 2.15 | 1.75 | 1.30 |
| 20.0 | 3.75 | 2.90 | 2.35 | 3.45 | 3.00 | 2.45 | 2.05 | 1.65 | 1.25 |
| 22.0 | 3.40 | 2.70 | 2.25 | 3.30 | 2.85 | 2.35 | 2.00 | 1.60 | 1.25 |
| 24.0 | 3.10 | 2.55 | 2.15 | 3.20 | 2.70 | 2.25 | 1.90 | 1.50 | 1.20 |
| 26.0 | 2.85 | 2.40 | 2.05 | 2.80 | 2.55 | 2.15 | 1.85 | 1.45 | 1.15 |
| 28.0 | 2.35 | 2.25 | 1.95 | 2.40 | 2.40 | 2.05 | 1.70 | 1.36 | 1.15 |
| 30.0 | 1.85 | 2.00 | 1.90 | 1.95 | 2.10 | 1.95 | 1.55 | 1.30 | 1.10 |
| 32.0 | 1.50 | 1.60 | 1.70 | 1.60 | 1.70 | 1.80 | 1.45 | 1.25 | 1.05 |
| 34.0 | 1.15 | 1.25 | 1.30 | 1.25 | 1.35 | 1.45 | 1.35 | 1.15 | 1.00 |
| 36.0 | 0.85 | 0.90 | 0.95 | 0.95 | 1.05 | 1.10 | 1.30 | 1.10 | 1.00 |
| 38.0 | 0.60 | 0.65 | 0.65 | 0.70 | 0.75 | 0.80 | 1.15 | 1.05 | 0.95 |
| 40.0 | | 0.40 | 0.40 | 0.45 | 0.50 | 0.55 | 0.90 | 1.00 | 0.90 |
| 42.0 | | | | | | | 0.75 | 0.85 | 0.90 |
| 44.0 | | | | | | | 0.56 | 0.65 | 0.75 |
| 46.0 | | | | | | | | 0.45 | 0.50 |
| ↙ % | I | 100 | | | 100 | | | 100 | |
| | II | 100 | | | 100 | | | 100 | |
| | III | 75 | | | 100 | | | 100 | |
| | IV | 75 | | | 100 | | | 100 | |